


ONE CLAD SB-2

Aluminium Cladding

www.fortepespa.ie



OneClad SB-2 is perfect for architectural designs, our cladding combines aesthetic appeal with a low-carbon footprint, promoting eco-friendly construction practices.

Lightweight, durable, and recyclable, it is engineered to meet the demands of sustainable architecture.

Product Specification

BOARD: Alcoa aluminum alloy 6063A, the lowest carbon footprint billet! With greater strength retains the same good surface finish qualities and affinity for anodizing.

Our products are manufactured under ISO 14001 and ISO 50001, ensuring our commitment to effective environmental management and sustainability.

ALUMINIUM GRADE: 6063A – Low Carbon Footprint.

Colour Range – Any RAL Available

FINISH: Interpon Qualicoat Class 1 & 2 performance Qualicoat coating material compliant with BS EN 12206:2021.

POWDER COATING: 60–70 microns. Interpon D Texture ISR coating provides corrosion protection and chemical resistance, designed for exterior exposure with good weather resistance from just one application. The coating sustains a longer lifespan.

FIRE RATING: A2-s1, d0.



📍 Greenogue Business Park, 623 Jordanstown Avenue,
Jordanstown, Rathcoole, Co. Dublin, D24 A9RW

☎ +353 1 6265197 ✉ info@fortepespa.ie [in](#)



Benefits

FIRE SAFETY

- Meets international fire safety standards for various buildings.
- Fire resistance A2ISD0.

NO ROTTING ISSUES

- Prevents rotting, enhancing safety, appearance and longevity.

LIGHTWEIGHT BUILD

- Easier to handle, install, and replace due to lightweight aluminium.

SUSTAINABILITY

- Contains no VOCs, making it eco-friendlier than liquid coatings. Up to 70% lower carbon than 6063 T6.

DRAINAGE SOLUTION


- OneClad can be integrated with our gutter solution.

COMPONENTS INTEGRATION

- All AlumExperts products are integrated and can fit any balcony design and terraces.
- Easy installation: join installation. This method allows the removal of a specific board without having to remove the other installed boards.

Our Aluminium vs the rest

Average global CO2e emissions per ton aluminium*



* Source: Average data per CRU Aluminium Cost Model 2020 and CRU Bauxite and Alumina Cost Model 2020.




📍 Greenogue Business Park, 623 Jordanstown Avenue, Jordanstown, Rathcoole, Co. Dublin, D24 A9RW

☎ +353 1 6265197 ✉ info@fortepespa.ie 

ONE CLAD

Aluminium Cladding

One Clad SB-2



BOARD DIMENSIONS

LENGTH: 4000 & 6000mm
WIDTH: 250mm

DEPTH: 16mm
MAX SPAN: 800mm

Coating Tests

Environmental and Durability Tests

Test	Standard
Acetic acid salt spray	ISO 9227
Constant humidity	ISO 6270-2
Sulphur Dioxide	ISO 22479
Permeability	EN12206-1 Par. 5.10
Chemical Resistance	N/A
Mortar Resistance	EN12206-1
Accelerated Weathering	ISO16474-2 (1000 hrs)
	ISO11507:QUV B 313 (300 hrs)
Exterior durability	ISO2810 (1 year)
Chalking	ASTM D4214-07

Mechanical Tests	Standard	Result
Flexibility	ISO 1519	Pass 5mm
Adhesion	ISO 2409	Gt0 (2mm crosshatch)
Erichsen Cupping	ISO 1520	Pass 5mm
Impact Resistance	ISO 6272-2	Pass 2.5 Joules (reverse & direct, 20 in lb)
Buchholz Hardness	ISO 2815	>80

Fire Classification Breakdown

- A2** Material of very limited combustibility. It contributes almost nothing to a fire.
- s1** Produces little to no smoke in the first 10 mins.
- d0** Produces no burning drops or particles in the first 10 minutes

Warranty

30 years against cracking, warping, rotting, and any material or manufacturing flaws.
60 years design life.

